

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of controlling a wireless communication link in a transmitter of a wireless communication system that automatically requires by a receiving party a second transmission from ~~a receiving party~~ to a transmitting party to the receiving party, the method comprising:

transmitting data from the transmitter at the transmitting party using at least one of an initial coding rate or an initial transmission power value to the receiving party;

receiving a second transmission request signal from the receiving party; and

performing the second transmission from the transmitter at the transmitting party by decreasing the initial coding rate and increasing the transmission power according to the second transmission request, and without requiring channel environment information of the wireless communication link,

wherein the decrease of the initial coding or the increase of the transmission power is performed in ~~fix a fixed~~ or flexible pattern.

2. (Canceled).

3. (Previously Presented) The method as claimed in claim 1, wherein the transmission power is returned to an initialized value, if a response signal is received from the receiving party after performing the second transmission.

4. (Previously Presented) The method as claimed in claim 1, wherein if the decrease of the coding rate for the second transmission reaches a lowest coding rate, the second transmission is continuously performed at the lowest coding rate, while the transmission power is continuously increased.

5. (Previously Presented) The method as claimed in claim 1, wherein a target power value is gradually increased while the second transmission is performed according to the second transmission request, and the transmission power is continuously increased.

6. (Previously Presented) The method as claimed in claim 1, wherein the second transmission is performed by maintaining the initial coding rate and increasing the transmission power according to the second transmission request.

7. (Currently Amended) A method of controlling a wireless communication link in a transmitter of a wireless communication system that automatically requires by a receiving party a

second transmission from ~~a receiving party to a transmitting party~~ to the receiving party, the method comprising:

transmitting data from the transmitter at the transmitting party using at least one of an initial coding rate or an initial transmission power value to the receiving party;

receiving a second transmission request signal from the receiving party; and

performing the second transmission from the transmitter at the transmitting party by decreasing the initial coding rate and increasing a number of multi-codes according to the second transmission request,

wherein channel environment information of the wireless communication link is not required at the transmitter for the performing the ~~data retransmission~~ second transmission.

8. (Canceled)

9. (Previously Presented) The method as claimed in claim 7, wherein the number of multi-codes is returned to an initialized value, if a response signal is received from the receiving party after performing the second transmission.

10. (Previously Presented) The method as claimed in claim 7, wherein if the decrease of the coding rate for the second transmission reaches to a lowest coding rate, the second

Serial No. **09/988,062**

Docket No. **HI-0054**

Amendment dated October 25, 2006

Reply to Office Action of July 28, 2006

transmission is continuously performed at the lowest coding rate, as the number of multi-codes is continuously increased.

11. (Previously Presented) The method as claimed in claim 7, wherein the second transmission is performed by maintaining the initial coding rate and increasing the number of multi-codes according to the second transmission request.

12. (Canceled)

13. (Previously Presented) The method as claimed in claim 1, wherein the decrease of the initial coding rate or the increase of the transmission power is performed in a predetermined pattern.